

PURCHASE MATERIAL: UHMW BLACK TIVAR 1000 VIRGIN MATERIAL
MANUFACTURER: POLY HI SOLDUR/QUADRANT PLASTICS
THICKNESS - TOLERANCE: +0.030"/ NO MINUS

PART NUMBER: MUHMW C | TT | THICK | WHERE TT = THICKNESS IN 1/10 INCHES
C = COLOUR (B = BLACK)
(W = WHITE)

EG. 1.000" UHMW BLACK TIVAR 1000 = MUHMWB10

MINIMUM MATERIAL PROPERTY VALUES
*REFERENCE DART REPORT DR-1041

YIELD TENSILE 2900 PSI
ULTIMATE TENSILE 4600 PSI
YIELD SHEAR 2200 PSI
ULTIMATE SHEAR 3500 PSI
YIELD BEARING 2800 PSI
ULTIMATE BEARING 4200 PSI
FLEXURAL MODULUS 105000 PSI

RELEASED
2011-06-13
RELEASED
2011-06-13

B	REFORMAT ADDED MATERIAL REQUIREMENTS FROM D2689 MANUFACTURER UPDATED (SEE PAR 11-105)	AJS	11.06.09
A	NEW ISSUE	RF	05.03.31
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	AJS		
CHECKED		DRAWING NO.	REV. B
MFG. APPR.		MUHMW	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		UHMW SHEET	NONE
DATE	11.06.09	COPYRIGHT © 2005 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	